

## Mini-LED Display Module

### Features:

- High Brightness Level from 1,000 to 5,000 nits
- Display Size Available from 5" to 65"
- High Contrast Ratio: 100,000:1
- Lower Power Consumption: Reduced by 30% to 50%
- Sunlight Readable

Part number: EB156-ML9-Q3419A-18

Product description: 15.6" mini LED embedded LCD module.

Local dimming zone: 960 zones

Brightness: 1,800 nits

LCD: AHVA

Resolution: 1920X1080px, Normally Black

Viewing Angle: 85/85/85/85 (Typ.)(CR>=10)

Color depth: 16.7M

Power consumption: 70 Watt.

Interface: LVDS

Operating Temperature: -30°C ~80°C



Storage Temperature: -30°C ~80°C

## Product profile





Please scan the QR code to download the detailed specifications.

## Perspective

Top View		Bottom View
		

Pin #	Symbol	Description	Note	Pin #	Symbol	Description	Note
1	N.C.	No Connection		26	N.C.	No Connection	
2	ICL	I2C Clock		27	N.C.	No Connection	
3	WP	Write Protection		28	CH2_0-	LVDS Channel 2, Signal 0-	
4	SDA	I2C Data		29	CH2_0+	LVDS Channel 2, Signal 0+	
5	N.C.	No Connection		30	CH2_1-	LVDS Channel 2, Signal 1-	
6	N.C.	No Connection		31	CH2_1+	LVDS Channel 2, Signal 1+	
7	LVDS_SEL	LVDS data format selection		32	CH2_2-	LVDS Channel 2, Signal 2-	
8	N.C.	No Connection		33	CH2_2+	LVDS Channel 2, Signal 2+	
9	N.C.	No Connection		34	GND	Ground	
10	N.C.	No Connection		35	CH2_CLK-	LVDS Channel 2, Clock -	
11	GND	Ground		36	CH2_CLK+	LVDS Channel 2, Clock +	
12	CH1_0-	LVDS Channel 1, Signal 0-		37	GND	Ground	
13	CH1_0+	LVDS Channel 1, Signal 0+		38	CH2_3-	LVDS Channel 2, Signal 3-	
14	CH1_1-	LVDS Channel 1, Signal 1-		39	CH2_3+	LVDS Channel 2, Signal 3+	
15	CH1_1+	LVDS Channel 1, Signal 1+		40	N.C.	No Connection	
16	CH1_2-	LVDS Channel 1, Signal 2-		41	N.C.	No Connection	
17	CH1_2+	LVDS Channel 1, Signal 2+		42	GND	Ground	
18	GND	Ground		43	GND	Ground	
19	CH1_CLK-	LVDS Channel 1, Clock -		44	GND	Ground	
20	CH1_CLK+	LVDS Channel 1, Clock +		45	GND	Ground	
21	GND	Ground		46	GND	Ground	
22	CH1_3-	LVDS Channel 1, Signal 3-		47	N.C.	No Connection	
23	CH1_3+	LVDS Channel 1, Signal 3+		48	Vcc	Power Supply Input Voltage 1	
24	N.C.	No Connection		49	Vcc	Power Supply Input Voltage 1	
25	N.C.	No Connection		50	Vcc	Power Supply Input Voltage 1	
				51	Vcc	Power Supply Input Voltage 1	

Note1: Please power supply according to the screen voltage



矽洋科技股份有限公司		1:1	MM
製圖	設計	校對	核准