Mini-LED Display Module

Features:

- High Brightness Level from 1,000 to 5,000 nits
- Display Size Available from 5" to 65"
- High Contrast Ratio: 100,000:1
- Lower Power Consumption: Reduced by 30% to 50%
- Sunlight Readable

Part number: EB050M192X1106L20A
Product description: 5” Mini-LED FALD Display Module
Local dimming zone: 192 zones
Brightness: 2000 nits
LCD: IPS
Resolution: 1024*600px, normally black
Viewing Angle: 80 / 80 / 80 / 80 (Typ.), CR≥10
Color depth: 16.7 M
Interface: LVDS
Operating temperature: -20°C ~ 70°C
Storage temperature: -30°C ~ 80°C

Product profile



Perspective view

Top View	Bottom View
	

The copyright belongs to EB-LCM. Any unauthorized use is prohibited.



PIN NO.	Symbol	PIN NO.	Symbol	PIN NO.	Symbol
1	VCOM	16	GND	31	LEDK
2	VDD	17	RXCLKIN-	32	LEDK
3	VDD	18	RXCLKIN+	33	LAR
4	NC	19	GND	34	UD
5	RESET	20	RXIN3-	35	VGL
6	STBYB	21	RXIN3+	36	NC
7	GND	22	GND	37	NC
8	RXIN0-	23	NC	37	VGH
9	RXIN0+	24	NC	39	LEDA
10	GND	25	GND	40	LEDA
11	RXIN1-	26	NC		
12	RXIN1+	27	NC		
13	GND	28	SELB		
14	RXIN2-	29	ANTD		
15	RXIN2+	30	GND		

The copyright belongs to EB-LCM. Any unauthorized use is prohibited.